

NEW Aluminium Flush Tilt & Turn Window



The NEW Stellar Flush Tilt & Turn window has a strikingly slim sash that sits flush against its frame and has elegantly concealed gearing to give you a contemporary, streamlined finish. It gives a dramatic expanse of glass that maximises light and views to create a sophisticated space that's popular across domestic installations.



- Double or triple glazed
- Wind load resistance to 1600Pa
- Water tightness to 300Pa
- Air permeability to 600Pa
- U-values
1.4 W/m²K - Double glazed.
0.98 W/m²K - Triple glazed.

Stellar colour range

STOCK						MADE TO ORDER					
	Signal White Flat/Matt RAL 9003	Anthracite Grey Flat/Matt RAL 7016	Anthracite Grey/ Signal White Flat/Matt RAL 7016 / 9003	Jet Black Flat/Matt RAL 9005	Jet Black/ Signal White Flat/Matt RAL 9005 / 9003		Cream Flat/Matt RAL 9001	Agate Grey Flat/Matt RAL 7038	Slate Grey Flat/Matt RAL 7015	Chocolate Brown Flat/Matt RAL 8017	Anthracite Grey Textured RAL 7016

Patented knock-in bead system - <i>fast fitting</i>	Concealed hardware for a sleek finish	Unique thermal break technology
Contemporary slim sightlines	Pre-gasketed	Internal glazing

Security:

- ⊕ PAS 24:2016 accredited system
- ⊕ Meets Approved Document Q
- ⊕ Secured by Design

Guarantees:

- ⊕ 10-year mechanical performance guarantee
- ⊕ 25-year surface finish guarantee
- ⊕ 10-year mechanical guarantee on hardware

Cill sizes:

- ⊕ 100mm
- ⊕ 150mm
- ⊕ 200mm

Bead sizes:

- ⊕ 28mm
- ⊕ 36mm
- ⊕ 44mm



Turn mode
for maximum ventilation and ease of cleaning outside pane.



Tilt mode
top ventilation position.

Features

- ⊕ Contemporary slim sightlines
- ⊕ Sash sits flush against the frame for a streamlined finish
- ⊕ Concealed hardware enhances the sleek finish

Sash weights and size limits

- ⊕ Available in larger sizes to create modern, light-filled living spaces
- ⊕ 1342mm x 2442mm
- ⊕ 1642mm x 2042mm
- ⊕ Fixed light: 5m².

HARDWARE

- ⊕ Robust internal hardware with multiple locking points ensures it meets the Building Regulations security requirement of PAS 24:2016 as standard
- ⊕ Gearing prevents window moving from tilt to turn and vice versa, enhancing safety
- ⊕ Opening restrictors can be added if needed for an extra level of safety
- ⊕ Concealed hinges and gearing
- ⊕ Extra security around hinge points
- ⊕ 3-dimensional adjustment of the pivot post
- ⊕ Easily adjustable pivot post and stay hinges.



BS 4873
KM711705
ALUMINIUM WINDOW
SYSTEMS SUPPLIER



BS 4873 / PAS24
KM711706
ENHANCED SECURITY
ALUMINIUM WINDOW
SYSTEMS SUPPLIER



BS 4873 / PAS24
KM711704
ENHANCED SECURITY
ALUMINIUM DOOR
SYSTEMS SUPPLIER



www.stellaraluminium.co.uk